

Conceal® Textured Caulk

You love the look of wood, not caulking. Conceal is lightly textured to simulate the natural roughness of wood and comes in 7 colors designed to complement the most popular stain colors. The caulking disappears into the woodwork, and your home is sealed from the elements. With Conceal, you don't have to see it to know it's there.



Why Use Conceal?

- Lightly textured to blend in with wood
- Superior elasticity, memory and adhesion
- Won't crack, tear or pull away
- Cleans up with soap and water
- Interior/exterior use
- Resistant to rainfall in 1-4 hours*
- Easy to tool
- Compatible with all Sashco stains
- Colors made to complement Transformation Stain®

* In severe conditions (under 45°F and/or 70%+ humidity), full rain resistance may take longer. Cover caulk with plastic sheeting if rainfall is expected within 24 hours after installation.



Alyster Plunger

10.5 cartridges come with Sashco's unique Alyster plunger.

A flexible telescopic diaphragm not only stops material flow, it actually pulls material back into the nozzle!

- **Tight Seal** — Increases shelf life and minimizes leakage.
- **Stop Flow** — The flexible telescopic diaphragm assures that material flow will stop when caulk gun pressure is released.

Before You Start: Good Tips to Know

Compatibility is important!

Any product already on the wood that contains waxes, non-drying oils, or silicones can interfere with the adhesion of Conceal, or most any caulk, and must first be removed. Conceal is compatible with all Sashco wood stains. If unsure about Conceal's compatibility with another product, please call Sashco before applying Conceal (1-800-767-5656).


Application Steps

Surface Preparation:

Best results are obtained when Conceal is applied to wood surfaces that:


- Are clean — free of mold/mildew, pollen, dust, oils, dirt, loose wood fibers and any old caulking residue
- Are dry — applying Conceal to damp wood may affect adhesion
- Have a surface temperature between 40°F and 90°F (4°-32°C).

Joint Design: To ensure best elasticity and use less caulk, insert backer rod into joints deeper than 1/2" (refer to the diagram for details).





Applying Conceal:

- Cut the nozzle at a 45° angle to desired bead size.
- Gun out a smooth bead.
- Tool with a damp foam brush or your finger to ensure a tight seal to both sides of the joint.
- Clean excess product off surfaces (before it cures) with a putty knife and/or a damp rag.



Clean Up & Storage

- Clean hands with warm water and soap.
- Tightly wrap nozzles of open cartridges with plastic wrap and a rubber band. Store in moderate temperatures.
- Dispose of Conceal in accordance with local regulations. Do not dispose of in drinking water supplies.



First Aid

EYES: Immediately flush with large quantities of water for at least 15 minutes. If irritation persists, see a medical doctor.

SKIN: Wash with soap and water and rinse thoroughly. Wash contaminated clothing before use.

INHALATION: Remove to fresh air.

INGESTION: If large quantities are swallowed, **Do Not Induce Vomiting** — seek medical help.

For additional application tips and information on other Sashco high performance products, visit www.sashco.com.



For additional information visit
www.sashco.com